

BTD

Optional 2nd measurement point



SUPPLY CHAIN MONITORING SOLUTIONS

A second measurement point inside of the container enables you to take action when the temperature rises / falls before your cargo is damaged.
Requires a connected device to transmit its data (!)

TECHNICAL SPECIFICATIONS

Cargo integrity and handling compliance	Temperature -30° to +65° Humidity 0% to 100%
Advanced modes	Configurable temperature and humidity range
SIM Card	Requires another device for sending data
Battery	3.200mAh Li-Ion, rechargeable, UN38.3 certified
Protection	IP65
Dimensions	95 x 80 x 26 mm
Weight	122 grams
Firmware and sensor control	Over the Air sensor configuration, Over the air firmware updates / modifications
Certifications	UN38.3, CE, MSDS, RoHs

-  SMALL, RECHARGEABLE, RED COLOR, EASY TO FIND
-  SECURE AND STABLE BLUETOOTH CONNECTION
-  FOR TEMPERATURE SENSITIVE GOODS
-  FLEXIBLE POSITION IN THE CONTAINER



Kirschen Global Security GmbH
Oranienstr. 6 10997 Berlin

Email: order@kirsensecurity.com
www.kirsensecurity.com



Confidential

This document may contain confidential information. It is intended only for the recipient(s). If you are not the intended recipient, you are hereby notified that the disclosure, copying, distribution or use of the contents of this transmission is strictly prohibited, and no privilege or protection has been waived.