

Lock P6

Asset Monitoring System



SUPPLY CHAIN MONITORING SOLUTIONS

Lock P6:

TECHNICAL SPECIFICATIONS

Unlock Methods	Authorization for unlocking via Kirsens A-type tracker. Unlocking activated by touch of the fingerprint spot
Color	Silver Grey big
Product Material	Lock Body: 6061 aluminum alloy ,Shackle: 303 Stainless Steel
Product Size	Lock Body: L97*W60*H23mm、Diameter of shackle: 8mm
Product Weight	Net Weight:210g、Gross Weight:270g
Surface Treatment	Lock body: Surface sandblasting anodized Shackle: Stainless Steel Color
Support	Kirsens A-type v3
Bluetooth Parameters	Bluetooth Version:5.0 Working frequency:2.4G Receiving sensitivity:-80dbm Transmitting power:4dbm
Encryption Mode	AES
Battery	Built-in 3.0V CR2 800mah lithium manganese battery
Service Life	Standby 365 days
Working Temperature	-30C +70C
Working Humidity	5% ~ 95% (without condensation)
Waterproof	IP65
Shackle Strength	Vertical Tension≥150kg, Side Direction Tension≥300kg



Kirsens Global Security GmbH
Oranienstr. 6 10997 Berlin

Email: order@kirsensecurity.com
www.kirsensecurity.com

